

ABARTH 500



| | | MANUAL TRANSMISSION | COMPETIZIONE |
|---|---|---|--|
| ENGINE | N. CYLINDER, POWER KW(CV) G/M MAX TORQUE NM G/M TURBO BORE X STROKE (mm) COMPRESSION RATIO ENGINE | 4 cylinders in line, 4 valves for cylinder, 1368 cm ³ 135 CV (99 KW) a 5500 G/M 206 NM A 3000 G/M (SPORT MODE) IHI RHF3-P 72X84 9,8:1 TJET | 140 CV (103 KW) 5500 G/M |
| PERFORMANCE | MAX SPEED (KM/H) ACCELERATION 0-100KM/H | 205 7.9 | 8.1 |
| TRANSMISSION | TRACTION GEARBOX | Front Manual 5 GEAR | Manual transmission AUTOMATIZED 5 GEAR |
| SUSPENSION | FRONT REAR | Mc Pherson with Anti Roll Bar Twist axle with Anti Roll Bar | |
| BRAKE | FRONT REAR | Front ventilated brake disc 284x22 mm Rear disc Ø 240 MM X 11 mm | |
| STEERING | TYPE | Electrically assisted power steering DUALDRIVE with "sport mode" | |
| CONSUMPTION AND ECOLOGICAL LEVEL | URBAN (L/100KM) COMBINED (L/100KM) EXTRA URBAN (L/100KM) CO2 EMISSION (GR/KM) ECOLOGICAL LEVEL | 8,5 6,5 5,4 155 EURO 5 CEE-F5 | 8,4 151 |
| WHEELS | ALLOY WHEELS | 16" with tyres 195/45 | |
| CAPACITIES AND WEIGHTS | FUEL TANK ROAD READY WEIGHT TOWABLE WEIGHT | 35 l 1035 800 Kg | 1045 |
| ELECTRICAL | BATTERY | 250 A / 50 Ah | |
| EXHAUST | EXHAUST GAS PIPE | Normal. | |
| FILTRO ARIA | FILTRO | Normal. | |
| SHOCK ABSORBER | FRONT AMMORTIZZATORI | Normal. Normal. | |
| HABITABILITY | SEATS | | |
| DIMENSION | WIDTH (mm) HEIGHT (mm) PASSO (mm) AXLE FRONT (mm) AXLE REAR mm) BOOT VOLUME (dm ³) | 1627 1480/1485(*) 2300 1415/1409(*) 1408/1402(*) 185 | |

(*) With 205/40 R17 tyres